

### Position contact indication

- Suitable for industrial isolation according to IEC/EN 60947-3 standard.
- The presence of the green strip guarantees physical opening of the contacts and allows operations to be performed on the downstream circuit in complete safety.



PB105265-40

DB122818

### iSW control switches (20, 32 A)

- IEC/EN 60669-1, iSW switch with indicator light.
- IEC/EN 60669-2-4, iSW switch without indicator light.

These switches are used for:

- Control (opening and closing of circuits under load). The 1P and 2P switches are available with or without indicator light.
- Disconnection, for switches without indicator light IEC/EN 60669-2-4.

### iSW switch-disconnectors (40 to 125 A)

#### IEC 60947-3





The switch-disconnectors combine the following functions:

- Control (opening and closing of circuits under load).

#### OF iSW auxiliary

- Mounted on the left, it indicates the "open" or "closed" position of the switch and has a normally open (NO) or normally closed (NC) contact.

## Catalogue numbers

20, 32 A iSW control switches				
Type	Rating	Voltage (Ue)		Width in 9 mm modules
<b>1P</b> 	20 A	250 V AC	<b>A9S60120</b>	2
	32 A	250 V AC	<b>A9S60132</b>	
<b>2P</b> 	20 A	250 V AC	-	2
		415 V AC	<b>A9S60220</b>	
	32 A	250 V AC	-	
415 V AC		<b>A9S60232</b>		
<b>3P</b> 	20 A	415 V AC	<b>A9S60320</b>	4
	32 A	415 V AC	<b>A9S60332</b>	
<b>4P</b> 	20 A	415 V AC	<b>A9S60420</b>	4
	32 A	415 V AC	<b>A9S60432</b>	
Operating frequency			50/60 Hz	
Accessories			<b>Module CA907012</b>	

PB105264-40

PB105265-40



Control switches



Control switches with indicator light

## Catalogue numbers (cont.)

20, 32 A iSW control switches with indicator light			
Type	Rating	230 V indicator light	Width in 9 mm modules
<b>1P</b> 	20 A	<b>A9S61120</b>	2
	32 A	<b>A9S61132</b>	
<b>2P</b> 	20 A	<b>A9S61220</b>	2
	32 A	<b>A9S61232</b>	
Operating frequency		50/60 Hz	
<b>Accessories</b>		<b>Module CA907012</b>	

Spare indicator lights for 20, 32 A iSW switches		
Type	Voltage (Ue)	
<b>Neon</b>		
Supplied with a red diffuser (Pack of 10)	230 V AC	<b>15111</b>
<b>Incandescent bulb (P=1.2 W)</b>		
Supplied with a red diffuser (Pack of 10)	12 V DC/AC	<b>15112</b>
	24 V DC/AC	<b>15113</b>
	48 V DC/AC	<b>15114</b>



Switch-disconnectors



40 to 125 A iSW switch-disconnectors				
Type	Rating	Voltage (Ue)		Width in 9 mm modules
<b>1P</b> 	40 A	250 V AC	<b>A9S60140</b>	2
	63 A	250 V AC	<b>A9S60163</b>	
	100 A	250 V AC	<b>A9S60191</b>	
	125 A	250 V AC	<b>A9S60192</b>	
<b>2P</b> 	40 A	415 V AC	<b>A9S60240</b>	4
	63 A	415 V AC	<b>A9S60263</b>	
	100 A	415 V AC	<b>A9S60291</b>	
	125 A	415 V AC	<b>A9S60292</b>	
<b>3P</b> 	40 A	415 V AC	<b>A9S60340</b>	6
	63 A	415 V AC	<b>A9S60363</b>	
	100 A	415 V AC	<b>A9S60391</b>	
	125 A	415 V AC	<b>A9S60392</b>	
<b>4P</b> 	40 A	415 V AC	<b>A9S60440</b>	8
	63 A	415 V AC	<b>A9S60463</b>	
	100 A	415 V AC	<b>A9S60491</b>	
	125 A	415 V AC	<b>A9S60492</b>	
Operating frequency		50/60 Hz		
<b>Accessories</b>		<b>Module CA907012 and CA907013</b>		